

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number  
**WO 2005/052980 A1**

(51) International Patent Classification<sup>7</sup>: **H01J 37/32**

(21) International Application Number:  
PCT/GB2004/004542

(22) International Filing Date: 27 October 2004 (27.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0326500.6 13 November 2003 (13.11.2003) GB

(71) Applicant (for all designated States except US): **OXFORD INSTRUMENTS PLASMA TECHNOLOGY LIMITED** [GB/GB]; Old Station Way, Eynsham, Oxford OX8 1TL (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SINGH, Nityalendra** [GB/GB]; 234 Ellan Hay Road, Bradley Stoke BS32

0HF (GB). **HALL, Simon** [GB/GB]; 6 Mead Road, North Weston, Portished, Bristol BS20 6RY (GB).


(74) Agent: **GILL JENNINGS & EVERY**; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: GAS PORT ASSEMBLY



(57) Abstract: A gas port assembly is provided for supplying or removing one or more gases to a powered electrode in a plasma processing chamber. The chamber has at least one electrode (11) to which an alternating electrical potential is applied in use, the assembly being electrically insulated from the electrode(s). The assembly comprises, a number of dielectric members (15) and a number of electrically conductive members (16). The members are arranged in a stack of alternating dielectric and electrically conductive members. Each member comprises at least one gas pathway for the passage of the gas(es), such that when stacked, the gas pathways are in communication with each other and the gas(es) are able to pass between an outer side of the stack and a chamber side of the stack. The members act as a capacitive divider to reduce high voltages within the assembly.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*